



DIMENSION	MEASURE	DIMENSION	MEASURE
APPLIANCE		MIN AREA of rear opening required with oven	0 cm ²
Product width	580 mm	MIN distance from cabinet to rear wall, with oven	0 mm
Product depth	500 mm	Indicates whether a ventilation opening in the top front side of cabinet is needed or not with oven. Default is "N"	No
Radius of product corner	6 mm	MIN Frontal gap required, with oven (2)	0 mm
Product height (MAX protrusion from the worktop)	48 mm	MIN frontal opening area required with oven	0 cm ²
Underneath the bearing area of the appliance	38 mm	WITH CABINET	
Distance between cut out and top frontal projection	14 mm	MIN worktop thickness with cabinet	0 mm
Distance between cut out and top lateral projection	11 mm	MAX worktop thickness with cabinet	0 mm
Plateau thickness	12 mm	Indicates whether a protection tray against heat or contact is needed. Default is "Y"	Yes
Gas outlet positioning	Rear right	MIN distance from bottom line of appliance to protection tray	20 mm
Gas outlet X positioning	31 mm	Indicates whether a ventilation opening in the tray is needed or not with cabinet	No
Gas outlet Y positioning	20 mm	Recess dimension X	0 mm
Power cable	With product	Recess dimension Y	0 mm
Power cable positioning	Rear right	Positioning dimension X by axis	0 mm
CUT OUT		Distance of the tray from the back panel/wall	0 mm
MIN front distance from cut-out to end worktop	0 mm	Indicates whether a divider is available	N/A
MIN rear distance from cut out to wall/furniture	70 mm	Indicates whether a ventilation opening in the back side of cabinet is needed or not. Default is "Y"	No
MIN lateral distance from cut out to wall/furniture	110 mm	Indicates the position of the opening in the back side of the cabinet.	N/A
MIN height from worktop to above furniture	400 mm	MIN Width of rear opening of the cabinet	0 mm
MIN cut out width	560 mm	MIN Depth of rear opening of the cabinet	0 mm
MAX cut out width	562 mm	MIN AREA of rear opening of the cabinet	0 cm ²
MIN cut out depth	480 mm	MIN distance from cabinet to rear wall	0 mm
MAX cut out depth	482 mm	Indicates whether a ventilation opening in the top front side of cabinet is needed or not. Default is "N"	No
MIN cut out radius	6.5 mm	MIN Frontal gap of the cabinet	0 mm
MAX cut out radius	8 mm	MIN frontal opening area of the cabinet	0 cm ²
FLUSH INSTALLATION		INSTALLATION SPACE	
Indicates whether a flush installation is possible. Default is "N"	No	Depth of immersion underneath the appliance	5 mm
MIN Milling rabbet width	0 mm	Width protruding area below bottom box	80 mm
MAX Milling rabbet width	0 mm	Depth protruding area below bottom box	72 mm
MIN Milling rabbet depth	0 mm	Protruding area: X positioning	10 mm
MAX Milling rabbet depth	0 mm	Protruding area: Y positioning	3 mm
Milling rabbet thickness	0 mm	ACCESSORIES FOR INSTALLATION	
Radius milling rabbet	0 mm	Gasket	Separate KIT
Flush installation KIT (2)	N/A	Clips	Separate KIT
Indicates the minum worktop thickness with standard installation for gas	20 mm	Injector KIT	Separate KIT
Indicates the maximum worktop thickness with standard installation for gas	60 mm	Elbow KIT	N/A
Indicates the minum worktop thickness with flush installation for gas	0 mm	COOKTOP HOOD INSTALLATION ONLY FOR GAS	
Indicates the maximum worktop thickness with flush installation for gas	0 mm	MIN distance from cooktop to above furniture	750 mm
WITH OVEN		MIN distance between cabinets above the cooktop	600 mm
Indicates whether the cooktop can be installed above oven. Default is "Y"	Yes	MAX distance between cabinets above the cooktop	750 mm
MIN worktop thickness with oven	0 mm		
MAX worktop thickness with oven	0 mm		
Indicates whether a protection tray against heat or contact is needed with oven. Default is "N"	No		
Indicates whether a ventilation opening in the back side of cabinet is needed or not with oven. Default is "Y"	No		
Indicates the position of the opening in the back side of the cabinet with oven	N/A		
MIN Width of rear opening required with oven	0 mm		
MIN Depth of rear opening required with oven.	0 mm		