



| DIMENSION | MEASURE | | DIMENSION | MEASURE | |
|--|-------------|----|---|---------------|-----------------|
| APPLIANCE | | | MIN AREA of rear opening required with oven | 0 | cm ² |
| Product width | 580 | mm | MIN distance from cabinet to rear wall, with oven | 0 | mm |
| Product depth | 510 | mm | Indicates whether a ventilation opening in the top front side of cabinet is needed or not with oven. Default is "N" | No | |
| Radius of product corner | 10 | mm | MIN Frontal gap required, with oven (2) | 0 | mm |
| Product height (MAX protrusion from the worktop) | 4 | mm | MIN frontal opening area required with oven | 0 | cm ² |
| Underneath the bearing area of the appliance | 42 | mm | WITH CABINET | | |
| Distance between cut out and top frontal projection | 10 | mm | MIN worktop thickness with cabinet | 20 | mm |
| Distance between cut out and top lateral projection | 10 | mm | MAX worktop thickness with cabinet | 50 | mm |
| Plateau thickness | 4 | mm | Indicates whether a protection tray against heat or contact is needed. Default is "Y" | Yes | |
| Gas outlet positioning | N/A | | MIN distance from bottom line of appliance to protection tray | 20 | mm |
| Gas outlet X positioning | 0 | mm | Indicates whether a ventilation opening in the tray is needed or not with cabinet | No | |
| Gas outlet Y positioning | 0 | mm | Recess dimension X | 0 | mm |
| Power cable | N/A | | Recess dimension Y | 0 | mm |
| Power cable positioning | Rear | | Positioning dimension X by axis | 0 | mm |
| CUT OUT | | | Distance of the tray from the back panel/wall | 0 | mm |
| MIN front distance from cut-out to end worktop | 0 | mm | Indicates whether a divider is available | N/A | |
| MIN rear distance from cut out to wall/furniture | 50 | mm | Indicates whether a ventilation opening in the back side of cabinet is needed or not. Default is "Y" | No | |
| MIN lateral distance from cut out to wall/furniture | 100 | mm | Indicates the position of the opening in the back side of the cabinet. | N/A | |
| MIN height from worktop to above furniture | 400 | mm | MIN Width of rear opening of the cabinet | 0 | mm |
| MIN cut out width | 560 | mm | MIN Depth of rear opening of the cabinet | 0 | mm |
| MAX cut out width | 562 | mm | MIN AREA of rear opening of the cabinet | 0 | cm ² |
| MIN cut out depth | 490 | mm | MIN distance from cabinet to rear wall | 0 | mm |
| MAX cut out depth | 492 | mm | Indicates whether a ventilation opening in the top front side of cabinet is needed or not. Default is "N" | No | |
| MIN cut out radius | 6.5 | mm | MIN Frontal gap of the cabinet | 0 | mm |
| MAX cut out radius | 8 | mm | MIN frontal opening area of the cabinet | 0 | cm ² |
| FLUSH INSTALLATION | | | INSTALLATION SPACE | | |
| Indicates whether a flush installation is possible. Default is "N" | Yes | | Depth of immersion underneath the appliance | 0 | mm |
| MIN Milling rabbet width | 583 | mm | Width protruding area below bottom box | 0 | mm |
| MAX Milling rabbet width | 585 | mm | Depth protruding area below bottom box | 0 | mm |
| MIN Milling rabbet depth | 513 | mm | Protruding area: X positioning | 0 | mm |
| MAX Milling rabbet depth | 515 | mm | Protruding area: Y positioning | 0 | mm |
| Milling rabbet thickness | 6 | mm | ACCESSORIES FOR INSTALLATION | | |
| Radius milling rabbet | 11.5 | mm | Gasket | Pre assembled | |
| Flush installation KIT (2) | Service KIT | | Clips | Separate KIT | |
| Indicates the minum worktop thickness with standard installation for gas | 0 | mm | Injector KIT | N/A | |
| Indicates the maximum worktop thickness with standard installation for gas | 0 | mm | Elbow KIT | N/A | |
| Indicates the minum worktop thickness with flush installation for gas | 0 | mm | COOKTOP HOOD INSTALLATION ONLY FOR GAS | | |
| Indicates the maximum worktop thickness with flush installation for gas | 0 | mm | MIN distance from cooktop to above furniture | 0 | mm |
| WITH OVEN | | | MIN distance between cabinets above the cooktop | 0 | mm |
| Indicates whether the cooktop can be installed above oven. Default is "Y" | Yes | | MAX distance between cabinets above the cooktop | 0 | mm |
| MIN worktop thickness with oven | 20 | mm | | | |
| MAX worktop thickness with oven | 50 | mm | | | |
| Indicates whether a protection tray against heat or contact is needed with oven. Default is "N" | No | | | | |
| Indicates whether a ventilation opening in the back side of cabinet is needed or not with oven. Default is "Y" | No | | | | |
| Indicates the position of the opening in the back side of the cabinet with oven | N/A | | | | |
| MIN Width of rear opening required with oven | 0 | mm | | | |
| MIN Depth of rear opening required with oven. | 0 | mm | | | |