



DIMENSION	MEASURE		DIMENSION	MEASURE	
APPLIANCE			MIN AREA of rear opening required with oven	0	cm ²
Product width	590	mm	MIN distance from cabinet to rear wall, with oven	0	mm
Product depth	510	mm	Indicates whether a ventilation opening in the top front side of cabinet is needed or not with oven. Default is "N"	No	
Radius of product corner	8.5	mm	MIN Frontal gap required, with oven (2)	0	mm
Product height (MAX protrusion from the worktop)	51	mm	MIN frontal opening area required with oven	0	cm ²
Underneath the bearing area of the appliance	39	mm	WITH CABINET		
Distance between cut out and top frontal projection	10	mm	MIN worktop thickness with cabinet	0	mm
Distance between cut out and top lateral projection	15	mm	MAX worktop thickness with cabinet	0	mm
Plateau thickness	7	mm	Indicates whether a protection tray against heat or contact is needed. Default is "Y"	Yes	
Gas outlet positioning	Rear right		MIN distance from bottom line of appliance to protection tray	20	mm
Gas outlet X positioning	34	mm	Indicates whether a ventilation opening in the tray is needed or not with cabinet	No	
Gas outlet Y positioning	37	mm	Recess dimension X	0	mm
Power cable	With product		Recess dimension Y	0	mm
Power cable positioning	Rear		Positioning dimension X by axis	0	mm
CUT OUT			Distance of the tray from the back panel/wall	0	mm
MIN front distance from cut-out to end worktop	0	mm	Indicates whether a divider is available	N/A	
MIN rear distance from cut out to wall/furniture	55	mm	Indicates whether a ventilation opening in the back side of cabinet is needed or not. Default is "Y"	No	
MIN lateral distance from cut out to wall/furniture	115	mm	Indicates the position of the opening in the back side of the cabinet.	N/A	
MIN height from worktop to above furniture	420	mm	MIN Width of rear opening of the cabinet	0	mm
MIN cut out width	560	mm	MIN Depth of rear opening of the cabinet	0	mm
MAX cut out width	562	mm	MIN AREA of rear opening of the cabinet	0	cm ²
MIN cut out depth	480	mm	MIN distance from cabinet to rear wall	0	mm
MAX cut out depth	482	mm	Indicates whether a ventilation opening in the top front side of cabinet is needed or not. Default is "N"	No	
MIN cut out radius	6.5	mm	MIN Frontal gap of the cabinet	0	mm
MAX cut out radius	8	mm	MIN frontal opening area of the cabinet	0	cm ²
FLUSH INSTALLATION			INSTALLATION SPACE		
Indicates whether a flush installation is possible. Default is "N"	No		Depth of immersion underneath the appliance	4	mm
MIN Milling rabbet width	0	mm	Width protruding area below bottom box	56	mm
MAX Milling rabbet width	0	mm	Depth protruding area below bottom box	75	mm
MIN Milling rabbet depth	0	mm	Protruding area: X positioning	6	mm
MAX Milling rabbet depth	0	mm	Protruding area: Y positioning	17	mm
Milling rabbet thickness	0	mm	ACCESSORIES FOR INSTALLATION		
Radius milling rabbet	0	mm	Gasket	Separate KIT	
Flush installation KIT (2)	N/A		Clips	Separate KIT	
Indicates the minum worktop thickness with standard installation for gas	20	mm	Injector KIT	Separate KIT	
Indicates the maximum worktop thickness with standard installation for gas	60	mm	Elbow KIT	N/A	
Indicates the minum worktop thickness with flush installation for gas	0	mm	COOKTOP HOOD INSTALLATION ONLY FOR GAS		
Indicates the maximum worktop thickness with flush installation for gas	0	mm	MIN distance from cooktop to above furniture	750	mm
WITH OVEN			MIN distance between cabinets above the cooktop	600	mm
Indicates whether the cooktop can be installed above oven. Default is "Y"	Yes		MAX distance between cabinets above the cooktop	750	mm
MIN worktop thickness with oven	0	mm			
MAX worktop thickness with oven	0	mm			
Indicates whether a protection tray against heat or contact is needed with oven. Default is "N"	No				
Indicates whether a ventilation opening in the back side of cabinet is needed or not with oven. Default is "Y"	No				
Indicates the position of the opening in the back side of the cabinet with oven	N/A				
MIN Width of rear opening required with oven	0	mm			
MIN Depth of rear opening required with oven.	0	mm			